

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

What is claimed is:

1. A light branching apparatus, comprising:

an optical splitter which splits an optical signal for a plurality of channels on a first optical fiber into at least a first optical channel signal on 5 a first channel of a second optical fiber and a plurality of second optical channel signals on a plurality of second channels of a third optical fiber; and

10 a first wavelength dispersion compensator which is provided for said first channel and compensates wavelength dispersion of said first optical channel signal due to said optical splitter.

2. The light branching apparatus according to claim 1, further comprising:

a second wavelength dispersion compensator which is provided for said plurality of second 5 channels and compensates wavelength dispersion of said plurality of second optical channel signals due to said optical splitter.

3. The light branching apparatus according to claim 1, wherein said first wavelength dispersion compensator compensates wavelength dispersion of said first optical channel signal due to said second 5 optical fiber, in addition to said wavelength

dispersion of said first optical channel signal due to said optical splitter.

4. The light branching apparatus according to claim 3, wherein said first wavelength dispersion compensator compensates said wavelength dispersion of said first optical channel signal due to said second optical fiber by difference in length between said second optical fiber and said third optical fiber on which said first optical channel signal is selectively propagated.

5. The light branching apparatus according to claim 4, further comprising:

an optical switch which switches a channel from one of said plurality of second channels to said first channel.

6. The light branching apparatus according to claim 1, further comprising:

said third wavelength dispersion compensator which is provided for said first channel and
5 compensates wavelength dispersion of said first optical channel signal due to said second optical fiber.

7. The light branching apparatus according to

claim 1, further comprising:

 said fourth wavelength dispersion compensator which is provided for a third channel of said second 5 optical fiber and compensates wavelength dispersion of a third optical channel signal inputted to said light branching apparatus due to said second optical fiber.

8. The light branching apparatus according to claim 1, wherein said plurality of optical channel signals are compensated in units of channels, and said first wavelength dispersion compensator includes at 5 least a first wavelength dispersion compensating element for the channel of said first optical channel signal.

9. An optical communication system comprising:
 a first optical fiber connected to a first station;
 a second optical fiber connected to a second 5 station;
 a third optical fiber connected to a third station; and

 a light branching apparatus, which comprises:
 an optical splitter which splits an optical 10 signal for a plurality of channels on said first optical fiber from said first station into at least a first optical channel signal on a first channel of

15 said second optical fiber and a plurality of second optical channel signals on a plurality of second channels of said third optical fiber; and

a first wavelength dispersion compensator which is provided for said first channel and compensates wavelength dispersion of said first optical channel signal due to said optical splitter.

10. The optical communication system according to claim 9, further comprising:

5 a second wavelength dispersion compensator which is provided for said plurality of second channels and compensates wavelength dispersion of said plurality of second optical channel signals due to said optical splitter.

11. The optical communication system according to claim 10, wherein said first wavelength dispersion compensator compensates wavelength dispersion of said first optical channel signal due to said second optical fiber, in addition to said wavelength dispersion of said first optical channel signal due to said optical splitter.

12. The optical communication system according to claim 11, wherein said first wavelength dispersion compensator compensates said wavelength dispersion of

said first optical channel signal due to said second
5 optical fiber by difference in length between said
second optical fiber and said third optical fiber on
which said first optical channel signal is selectively
propagated.

13. The optical communication system according to
claim 12, further comprising:

an optical switch which switches a channel from
one of said plurality of second channels to said first
5 channel.

14. The optical communication system according to
claim 9, further comprising:

said third wavelength dispersion compensator
which is provided for said first channel and
5 compensates wavelength dispersion of said first
optical channel signal due to said second optical
fiber.

15. The optical communication system according to
claim 9, further comprising:

~~said fourth wavelength dispersion compensator~~
which is provided for a third channel of said second
5 optical fiber and compensates wavelength dispersion of
a third optical channel signal inputted to said light
branching apparatus due to said second optical fiber.

16. The optical communication system according to
claim 9, wherein said plurality of optical channel
signals are compensated in units of channels, and said
first wavelength dispersion compensator includes at
5 least a first wavelength dispersion compensating
element for the channel of said first optical channel
signal.

17. A light branching apparatus comprising:
an optical switch which switches a transmission
channel of a first optical channel signal on a first
optical fiber from a first channel on a second optical
5 fiber to a second channel on a third optical fiber;
a wavelength dispersion compensator which
compensates wavelength dispersion of said first
optical channel signal due to said second optical
fiber by difference in length between said second
10 optical fiber and said third optical fiber.

18. A light branching apparatus, comprising:
an optical splitter which splits at least a
first optical channel signal from an optical signal
~~for a plurality of channels on a first optical fiber~~
5 to transmit onto a first channel of a second optical
fiber; and
a first wavelength dispersion compensator which
is provided for said first channel and compensates

wavelength dispersion of said first optical channel
10 signal due to said second optical fiber.

19. The light branching apparatus according to
claim 18, further comprising:

a second wavelength dispersion compensator
which is provided for a second channel of said second
5 optical fiber, and compensates wavelength dispersion
of a second optical channel signal supplied on said
second channel due to said second optical fiber.